

Moulded Case Circuit Breakers (MCCB)

M series

(With Intertek Test Report & Certificate)



**M63L
(2P/3P)**

rating (A)	cat. no. 2 pole	cat. no. 3 pole	Sym.	r.m.s (kA) lcu / lcs
20	M63L202P	M63L20	690V	8/4
32	M63L322P	M63L32	500V	10/5
40	M63L402P	M63L40	440V	15/8
50	M63L502P	M63L50	415V	25/18
63	M63L632P	M63L63	230V	35/25

Shunt trip 240VAC cat. no. SC63



**M100L
(3P)**



**M100L
(4P)
*N-PROTECTED**

rating (A)	cat. no. 3 pole	cat. no. 4 pole	Sym.	r.m.s (kA) lcu / lcs
20	M100L20	M100L204P	690V	8/4
32	M100L32	M100L324P	500V	20/10
40	M100L40	M100L404P	440V	25/17
50	M100L50	M100L504P	415V	35/26
63	M100L63	M100L634P	230V	50/35
80	M100L80	M100L804P		
100	M100L100	M100L1004P		

Shunt trip 240VAC cat. no. SC100



**M225L
(3P)**

rating (A)	cat. no. 3 pole	Sym.	r.m.s (kA) lcu / lcs
125	M225L125	690V	8/4
160	M225L160	500V	25/10
200	M225L200	440V	35/20
225	M225L225	415V	50/37
		230V	70/50

Shunt trip 240VAC cat. no. SC225



**M400L
(3P)**

rating (A)	cat. no. 3 pole	Sym.	r.m.s (kA) lcu / lcs
250	M400L250	690V	10/5
315	M400L315	500V	25/10
350	M400L350	440V	35/25
400	M400L400	415V	50/37
		230V	80/60

Shunt trip 240VAC cat. no. SC400



*** NOTE: TERMINALS BUSBARS ARE PROVIDED
FOR M400L FRAME SIZE**