

Consumer Unit (Insulating Material)



Technical Data

Application

DB enclosure suitable for fitting devices with maximum rating of 63A

Suitable for domestic and commercial installations.

As per IEC Standard requirements, we strongly advise to use consumer units with ABS Fire Retardant (FR) for better protection against hazardous continuous burning in case of fire.

Surface mounting type.

Material : High Impact PS

type	no. of row	way / row	mod. way	cat. no
8 way	1	8	8	MG0800N
10.5 way	1	10.5	10.5	MG1050N
15.5way	1	15.5	54	MG1550N
18.5way	1	18.5	17	MG1850N
23 way	1	23	23	MG2300N
*30 way	2	15	30	MG3000N
*45 way	3	15	45	MG4500N
*54 way	3	18	54	MG5400N

* Non-transparent cover

Surface mounting type. (non-transparent cover) Material : High Impact PS Fire Retardant (FR) to IEC 60695-2-11

type	no. of row	way / row	mod. way	cat. no
15.5 way	1	15.5	15.5	MG1550FR
18.5 way	1	18.5	18.5	MG1850FR
23 way	1	23	23	MG2300FR
30 way	2	15	30	MG3000FR
45 way	3	15	45	MG4500FR
54 way	3	18	54	MG5400FR

